

Single phase
Dual MPPT inverters
X1-Boost



Simple.
Reliable.
Efficient



High Efficiency



Wide Voltage Range



'Smart Plug'
Load Control



Remote Monitoring

X1-Boost

SolaX have developed a range of single phase inverters unrivalled in the industry for their quality, reliability and efficiency. The SolaX single phase inverters boast a wide MPPT voltage range to allow for more energy harvesting and have a maximum input voltage of 580V, with a maximum efficiency of 97.6%. In addition, SolaX single phase muffins are IP65 rated, have no internal fan and come with optional 'plug & play' WIFI. The dual MPPT 'Boost' range is also compatible with the new SolaX 'Smart Plug' which allows for device remote control.





X1-BOOST (SINGLE PHASE)

X1-3.0-T-N	X1-3.3-T-N	X1-3.6-T-N	X1-4.2-T-N	X1-4.6-T-N	X1-5.0-T-N
X1-3.0-T-D	X1-3.3-T-D	X1-3.6-T-D	X1-4.2-T-D	X1-4.6-T-D	X1-5.0-T-D

INPUT (DC)

Max.recommended PV power[W]	4500	4950	5400	6300	6900	7499
Max.DC voltage [V]	600	600	600	600	600	600
Nominal DC operating voltage [V]	360	360	360	360	360	360
Max. input current [A]	12/12	12/12	12/12	12/12	12/12	12/12
Max. short circuit current [A]	14/14	14/14	14/14	14/14	14/14	14/14
MPPT voltage range[V]	70-580	70-580	70-580	70-580	70-580	70-580
Start operating voltage[V]	100	100	100	100	100	100
No. of MPP trackers / Strings per MPP tracker	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)	2(1/1)

OUTPUT AC

Nominal AC power [VA]	3000	3300	3680	4200	4600	5000
Max. AC power [VA]	3300	3630	4048	4620	5060	5500
Nominal grid voltage(AC voltage range) [V]	220/230/240; 180~280					
Nominal grid frequency/range [Hz]	50/60; ±5					
Nominal AC current [A]	13	14.3	16	18.3	20	21.7
Max. AC current [A]	14.3	15.8	17.6	20.1	22	21.7
Displacement power factor	0.8 leading ~ 0.8 lagging					
THDi, rated power [%]	<2					

EFFICIENCY

MPPT efficiency [%]	99.9
Euro efficiency [%]	97.0
Max. efficiency [%]	97.8

POWER CONSUMPTION

Standby consumption (Night) [W]	<0.5
---------------------------------	------

STANDARD

Over voltage protection	YES
Over current protection	YES
DC isolation impedance monitoring	YES
Ground fault current monitoring	YES
DC injection monitoring	YES
RCD protection	YES
Safety	IEC62109-1/-2
EMC	EN 61000-6-1 / EN 61000-6-2 / EN 61000-6-3
Certification	VDE4105 / G98 / G99/ AS4777 / EN50549 / CEI0-21

ENVIRONMENT LIMIT

Degree of protection(according to IEC60529)	IP65
Operating temperature range [°C]	-25~+60(derating at 45)
Max. operation altitude [m]	<2000
Humidity [%]	0~100 (condensation)
Storage temperature [°C]	-25~+60
Typical noise emission [dB]	25

DIMENSION AND WEIGHT

Dimensions(WxHxD) [mm]	341.5*430*143
Weight[kg]	13.5 13.5 13.5 14.5 14.5
Cooling concept	Natural
Topology	Non-isolated
Communication interfaces	Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade
LCD display	Yes
Standard warranty [years]	12

*Can be modified without notice.(AU-V1)